



SpeechLine Digital Wireless CHG 4N - 4 bay network charger

FEATURES

- Seamless network integration
- 4 individual charging bays
- Battery status indication for each bay
- Full remote control

The CHG 4N is a network enabled charger featuring four individual charging bays. These can either be used for the SL Bodypack DW or the SL Handheld DW. Each bay is combined with 4 LEDs to indicate the corresponding battery status of the mobile device.

The flexible network interface provides IPv4 and IPv6 compatibility for seamless integration. All settings and status information can be monitored and remote controlled with the Sennheiser Control Cockpit.

DELIVERY INCLUDES

- CHG 4N
- External power supply (EU, UK, US or AU version)
- Quick guide
- Safety guide

PRODUCT VARIANTS

CHG 4N EU	Art. No. 506800
CHG 4N UK	Art. No. 506801
CHG 4N US	Art. No. 506802
CHG 4N AU	Art. No. 506803

ARCHITECT'S SPECIFICATION

The charger shall be network-enabled and shall be capable of simultaneously charging up to four handheld and/or bodypack transmitters of the Sennheiser SpeechLine Digital Wireless series. Four colored LEDs at each charging bay shall indicate charge status.

The charger shall have an RJ-45 network socket and shall support IPv4 and IPv6 network addressing. In addition, the charger shall support the Media Control Protocol to provide for remote control and status monitoring via the Sennheiser Control Cockpit software or a media control system.

The charger shall operate on 12 V DC input voltage supplied from an external power supply unit, the input current shall be maximum 1.1 A. Charging voltage shall be 5 V DC, charging current shall be maximum 1 A per charging bay. The power consumption shall be 2.5 A.

Charging time for full charge shall be approximately 2 hours. Operating temperature shall range from 0 °C to 45 °C (32 °F to 113 °F). Dimensions shall be 270 x 100 x 102 mm (10.63" x 3.94" x 4.02"). Weight (unequipped and without power supply unit) shall be approximately 1.1 kg (2.43 lbs).

The charger shall be the Sennheiser CHG 4N.



SPECIFICATIONS

Network protocol	Media Control Protocol IPv4 (DHCP, manual) / IPv6
Power supply	12 V DC
Current consumption	2.5 A
Network socket	RJ 45
Dimensions	270 x 100 x 102 mm (10.6" x 3.9" x 4")
Weight	1100 g
Charging bays	4
Charging voltage per bay	5 V
Charging current per bay	1 A
Charging status indicator	4 LEDs per bay (red, yellow, green, green)
Charging time for full charge	SL Handheld DW: 2 h SL Bodypack DW: 2 h
Operating temperature	0 °C to 45 °C (32 °F to 113 °F)



SpeechLine Digital Wireless CHG 4N - 4 bay network charger

DIMENSIONS

